



## Technical Data

### Areas of Use

Designed for use as part of a UHS maintenance program. Compatible with 1000-3000 rpm equipment.

- Hotel and office lobbies
- Hospitals, nursing homes
- Schools, universities
- Supermarkets, malls, retail stores
- Any facility suitable for a UHS maintenance program.

### Specifications

Available Sizes .....	4/1G
Physical State .....	Liquid
Color .....	Milky White
Fragrance .....	Floral
Specific Gravity .....	1.01
pH .....	8.0
<b>HMIS Hazard Rating</b>	
Health .....	1
Flammability .....	0
Reactivity .....	0
Personal Protection .....	A

### What the Pros Know


Before burnishing make sure the floor is clean and free of grit. This eliminates yellowing or darkening and greatly extends the life of the floor finish. Use of UHS restorers that are applied through an auto scrubber provide a highly efficient means of maintaining resilient flooring. UHS restorers add moisture back to finish and reduce the likelihood of powdering

- Repairs scuffs/abrasions - Restores gloss
- Concentrated - Long dilution ratios
- Water-based, Non-flammable - User friendly
- Prolongs life of floor finish - Overall labor savings
- Versatile - Mop on or apply through automatic scrubber
- Non-film forming polymers - Won't trap soil
- Improves slip resistance - Added safety

METEOR provides improved labor efficiency by allowing you to combine two cleaning tasks into a one-step process. The special blend of non-film forming polymers and detergents provides gloss restoration and light cleaning, all in one step. METEOR works on any UHS finish, on any type of flooring surface that is compatible with UHS equipment. METEOR is designed for use with 1000 to 3000 rpm equipment. Regular use of METEOR will fill scratches, reduce scuffing and improve slip resistance.

### Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work. See label for complete directions and use only as directed.



Dust mop to remove dry soil. If floor is heavily soiled, wet clean with STROBE, neutral pH cleaner, prior to applying METEOR.



**Mop Application:** Mop the floor with a dilution of METEOR diluted at 1:16 (8 ounces per gallon of water). Allow to dry, then burnish.



**Automatic Scrubber Application:** Apply METEOR through an automatic scrubber at a dilution of 1:20 (6 ounces per gallon of water). Dispense diluted restorer from machine, scrub and pickup in a single pass. Allow to dry, then burnish. Consult your Triple S representative for the proper pad selection.



May also be used as a spray buff solution, dilute 1:1 when used as a spray buff.

Use with mop  
or auto scrubber

Clean and  
restore gloss  
in one step

Prolongs life of  
floor finish

