

SHOP CLEAN

**HIGH POWERED DEGREASER
DESINTEGRADOR DE GRASA INDUSTRIAL**



Technical Data

Areas of Use

Degreaser for super heavy degreasing. Highly concentrated for removal of heavy grease and baked on soils.

- Industrial cleaning of heavy grease deposits, cutting and lubricating oils, inks and rubber tire marks.
- Removes baked on grease in ovens, grills, fans, filters and deep fat fryers.

Specifications

Available Sizes.....	4/1G, 5G, 55G
Physical State	Liquid
Color	Dark Red
Fragrance	Clean
Foaming	Low-Moderate
Free Rinsing	Yes
Petroleum Distillates	None
Viscosity	Thin
Phosphates	2.25%
Specific Gravity	1.037
pH (undiluted)	13
HMS Hazard Rating	
Health	2
Flammability	0
Reactivity	0
Personal Protection	B

What the Pros Know

This product provides a three-way approach to attacking greasy soil. The three-ways are solvency, emulsification, and saponification (by making a soap out of the grease). No matter what the grease, fat, or oil type, this product assures outstanding results.

- Super heavy degreaser - Quickly removes heavy grease and oil
- Surfactant built water-based solvents - Penetrate, emulsify and suspend soils
- Variable dilutions - Single product handles multiple applications
- Corrosion inhibitors - Ideal for dip soak tanks
- Controlled foam - Can be used in mechanical devices, saves time

Versatility and effectiveness are the highlights of this high powered cleaner-degreaser. Diluted with water this product is an ideal cleaner in commercial, industrial and institutional facilities. Effectively clean light soils from common surfaces or grease laden soils from industrial equipment and parts. It provides outstanding performance when applied by mop, brush, trigger sprayer, sponge, pressure sprayer, steam cleaner, automatic scrubber or in hot or cold soak tanks.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



GENERAL CLEANING: Dilute 1:16 (8 ounces per gallon of water) for heavily soiled concrete floors. Scrub or soak. Remove soiled solution and rinse. Dilute between 1:64 and 1:32 (2-4 ounces per gallon of water) for walls and high touch surfaces. Do not use on windows or glass.



KITCHEN CLEANING: Dilute 1:10 (12 ounces per gallon of water) for removing grease splatter around stoves, vent hoods, fans, blowers, and appliances. Boil out deep fat fryer, be sure to use exhaust vent or fan. To soften and remove baked-on grease on filters, fans, and stove parts, soak overnight, preferably in covered container. Scrub as needed and rinse.



INDUSTRIAL CLEANING: Dilute 1:16 (8 ounces per gallon water, or more as required) Cleans heavily soiled equipment and parts. Scrub or allow to soak. Rinse. This product can be used with pressure washing equipment.

SPECIAL USES: Removes black marks from flooring, cleans whitewall tires or vinyl.

Multiple applications

Controlled foam

Corrosion inhibitors

