



**NewAge**

# REPLAY MAINTENANCE CLEANER

## CLEANER FOR HARDWOOD FLOORS



### Technical Data Sheet

#### Environment, Health & Safety

- No alcohols
- No ammonia
- pH Neutral
- Non-hazardous

#### What the Pros Know

Preventative Maintenance will extend the life of your floor finish. Simple steps such as placing walk-off mats in door ways to keep out dirt and grit and avoiding excess moisture from tracked in water or leaks will prolong the life of your floor.

Having a planned daily maintenance schedule of dry mopping or damp mopping over spills can help reduce overall labor costs.

Periodic maintenance steps will be needed to keep the look and feel of the finish up to your standards. With this step, an autoscrubber or 175 rpm buffer with a white pad is used with the NewAge Replay Maintenance Cleaner to give a more thorough, deep cleansing. This will minimize the chance of contamination from damaging the floor and reducing overall labor costs.

#### Description

A waterborne, environmentally responsible cleaner specifically formulated for use in the preparation of old wood sport floors, or for periodic maintenance to clean all polyurethane finished wood floors without leaving any residue. NewAge Replay Maintenance Cleaner is a concentrate, to be diluted with water according to directions.

#### Recommended Use

- Aluminum oxide, ceramic, and other factory prefinished floors
- Basketball courts
- Volleyball courts
- Racquetball
- Badminton courts
- Multi-purpose gym and stage floors
- Aerobic floors

#### Features

- Formulated for use on all waterborne or oil-modified polyurethane finishes
- For deep cleaning and periodic maintenance
- For spot cleaning of food spills and other stains
- Leaves no oily or waxy residue
- pH neutral
- Nonflammable

pH neutral

Formulated for use with all urethane finishes

Virtually odorless

No oily or waxy residues

Excellent for spot & deep cleaning



## DIRECTIONS FOR USE:

SHAKE WELL BEFORE USING.

IMPORTANT! NEVER POUR CLEANER DIRECTLY ONTO THE FLOOR.

### FOR DAILY MAINTENANCE OF FINISHED FLOORS:

1. Sweep or dust mop (with untreated mop only) daily to remove dust, grit or other abrasive particles.
2. Lightly mist your clean mop head with diluted (1 part cleaner to 8 parts water) Replay Maintenance Cleaner Concentrate. Replace soiled mop covers as necessary. (Continued use of soiled covers will cause streaking.)
3. For spills or spots, damp wipe with Replay Maintenance Cleaner Concentrate diluted at the 1 to 8 ratio.

NOTE: DO NOT USE ANY DUST MOP TREATMENTS.

### FOR PERIODIC MAINTENANCE OF FINISHED FLOORS:

1. Dilute 1 part Replay Maintenance Cleaner Concentrate to 8 parts water for a tacking solution. Tack with a well wrung-out cotton towel wrapped around a push broom. Be sure to clean towels regularly and change the solution as needed.
2. Shoe marks and scuffs can be removed by using a white pad and a low or variable-speed buffer (175 rpm) with a (1:8) solution of Replay Maintenance Cleaner Concentrate. Lightly mist the floor with the solution as you buff. Periodically clean or replace white pad. Continued use of soiled pads will cause streaking.
3. Make sure all residue from the white pad buffing/cleaning procedure is removed from floor surface by immediately tacking the surface with water dampened, well wrung-out cotton towels.
4. For deep cleaning dilute 1 part Replay Maintenance Cleaner Concentrate to 5 parts water to be used as a spray-buff solution with a white pad and a low or variable-speed buffer (175 rpm).

**STORAGE:** FREEZE-THAW STABLE. Product should always be stored in a climate controlled environment. Do not store above 100° F. If frozen, allow product to thaw out at room temperature before applying.

**CLEAN-UP:** Clean all tools and equipment with water.

## SPECIFICATIONS/PHYSICAL DATA:

### Physical Characteristics:

**Ingredients** - Water (7732-18-5), anionic and nonionic surfactants (Proprietary), and glycol ether solvents (Proprietary).

**Color** - Brilliant purple solution (wet)

**pH** - 6.0 - 8.0

**Solids** - 2%

**Viscosity** - (#4 Ford cup @ 25°C) 10 seconds

**Density** - 8.39 lbs./gallon (1.01 S.G.)

**Packaging** - 5-gallon plastic pail - 32008 • 1-gallon plastic bottle - 32009

### Application Characteristics:

**Clarity** - Negligible residue (dry)

**Leveling** - N/A

**Defoaming** - N/A

**Drying Time** - 15 - 20 minutes

**Application Tools** - Varies with task; see label

**Gloss Level** - N/A

**Odor** - Non-offending

**Flash Point** - Non-flammable

**Stability** - One year shelf life in unopened container

**VOC** - Does not exceed 3%

**Coverage** - N/A

**Percent Cured After 24 Hours** - N/A

**Maximum Cure** - N/A