



Product Information

SSS MicroPower Mop – Wash Instructions

The following procedure for machine-washing MicroPower mops will assure maximum performance and longevity.

Wash:

	Operation	Minutes	WaterTemp	Water Level	Guidelines
1	Flush	2	120° F - 50° C	H	
2	Flush	2	140° F - 60° C	H	
3	Break/Suds	10	140° F - 60° C	L	6 oz. Built (non-solvent) detergent 100 lbs – 4g/kg (pH 8.5 – 11.5 maximum)
4	Rinse/Extract	3	140° F - 60° C	H	
5	Rinse/Extract	2	80° F - 27° C	H	
6	Rinse	2	80° F - 27° C	H	
7	Rinse	2	Cold	H	

Centrifugal Extraction: Bring to full speed (450 rpm) for 6 minutes and release.

Hydraulic Extraction: 250 PSI –8.3 bars for 3 minutes and release.

Drying: For best results, air-dry microfiber mops. If a dryer is used, tumble dry using low heat only.

- Handling/Processing:**
1. Do not use bleach to remove stains or for any other reason. Bleach will decrease the effectiveness and durability of the microfiber product.
 2. Do not use fabric softener.
 3. Do not wash with terry towels, regular mops or any other product that will shed lint.
 4. Separate different colored microfiber mops before their first wash.
 5. Microfiber mops can be hand washed using warm soapy water.

Note: Over time, the use of harsh chemicals such as those contained in bleach and fabric softeners will reduce the performance and longevity of microfiber mops.