



TUNDRA

SYNTHETIC FLOOR PROTECTANT

PISO SINTÉTICO PROTECTANT

Technical Data

Environment, Health & Safety

- Biodegradable
- Low Toxicity
- No Phosphates
- No Ozone Depleting Compounds
- No Known Carcinogens
- No Chlorine Bleach
- No Butoxyethanol
- No Petroleum Distillates
- Low VOC Level
- Recyclable Container

Specifications

SSS Item Numbers	48103
Available Sizes	2.5G
Color	Milky emulsion
Fragrance	Mild odor
pH	8.0 - 8.5
Non-volatile Solids	18.0 + 0.5%
Dry/Recoat Time	45 minutes min.
Slip Resistance	0.5 min. by ASTM-D2047
Durability	Excellent
Buffability	Spray buffing or high speed burnishing
Removability	With instant type strippers
Coverage	1800 - 2200 sp. ft./gal.
Detergent Resistance	Excellent
Viscosity	Water thin
VOC Content	0.54 lbs./gal.
Storage/Stability	1 year
Weight Per Gallon	8.54 lbs./gal.
Freeze/Thaw Stability	Keep from freezing

HMIS Hazardous Materials I.D. System

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

What the Pros Know


Using a microfiber applicator will result in exceptional flow and leveling properties and will help keep the finish off the baseboards.

Description

A new generation environmentally responsible synthetic floor finish designed to work on any type of synthetic floor due to its exceptional durability and flexibility. This synthetic floor finish is specifically formulated to work on rubberized flooring due to its elastic properties that will prevent cracking. Meets today's need for a product that contains no zinc or other heavy metals that can be harmful to wastewater treatment systems. This low odor finish has the flexibility needed to protect a synthetic floor, while being tough enough to stand up to excessive wear on that occurs on synthetic sport floors.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



PREPARATION: For new synthetic floors, make sure to check with the manufacturer regarding the warranty and specific maintenance recommendations before beginning. For older floors that are out of warranty, simply follow these steps to clean and prepare the floor for coating. If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with Savanna All Surface Cleaner following the directions accordingly to remove dirt and oils. If there is a heavy build-up of acrylic, urethane, or other film coatings, use Tornado Neutral pH Floor Stripper and follow directions accordingly. Follow with a thorough rinsing and allow floor to dry completely.

FINISHING: Apply 2 to 3 thin coats of product using a microfiber applicator or clean finish mop. Allow a minimum of 30 minutes drying time between coats. Repeat until a desired level of gloss is achieved.

RESTORATION: Dust mop or sweep thoroughly. Dilute Recharge Gloss Restorer according to directions and apply to floor with clean mop or automatic scrubber.

RECOATING: Dust mop or sweep thoroughly. Deep scrub using All Surface Cleaner diluted according to directions. Apply 1 or 2 coats of finish using a clean mop.



*Exception
Durability and
Flexibility*

Low Odor

*No Zinc or Other
Heavy Metals*



ECOLOGO

PRODUCT CERTIFIED FOR
REDUCED ENVIRONMENTAL
IMPACT. VIEW SPECIFIC
ATTRIBUTES EVALUATED:
UL.COM/EL
UL 2777

