

The logo consists of three stylized, overlapping 'S' characters. The top 'S' is orange with a black outline, while the two 'S' characters below it are solid black. They are arranged in a way that they appear to be interlocking or overlapping.

SSS

- High Productivity
- No Filling or Dumping
- Automatic Mixing

The text is in a bold, orange, sans-serif font. It is positioned on a black, angular background that appears to be part of the machine's housing.

HI-FLOW W EXTRACTOR



SSS[®] HI-FLOW EXTRACTOR

More for Your Dollar

The SSS Hi-Flow Extractor will save you 30% to 40% of the labor time you are now spending on carpet cleaning. How? By eliminating the *non-productive time* now spent in filling and emptying buckets and tanks. No longer will you have to stop cleaning every 15 minutes to dump and fill. Every time you stop, 5 to 10 minutes of cleaning time is lost. Lost time costs you money.

Elimination of the on-board solution tanks also reduces the weight of the extractor. A self-contained extractor with seven gallons of solution can weigh over 110 pounds. The SSS Hi-Flow weighs only 36 pounds. It is easy to maneuver. It is less tiring to operate and this increases cleaning productivity.

Improved Cleaning

The cleaning solution flow rate is 3 gallons per minute. This is more than *double* the flow rate of most units. The increased amount of cleaning solution flowing through the carpet fibers means better cleaning action. Soil and contaminants are washed away easier and faster. Add to this the powerful vacuum that draws out 10% more dirt carrying solution than other extractors. The result is a cleaner and drier carpet in less time. By combining several hose lengths you can clean an area up to 500 feet across.



Automatic Mixing

The cleaning concentrate is automatically mixed with the water. Just set the required mixing rate and turn on the machine. Also standard on the Hi-Flow is a pre-spotter attachment with a 25' hose. It automatically mixes your pre-spotter and makes it easy to treat trouble spots as you go. The optional Upholstery Kit can make furniture cleaning easier.

Carpet Care System

In the Pre-Spotter attachment use SSS Pretreat & Traffic Lane Cleaner. In the automatic dispensing bottle we recommend SSS Carpet Rinse diluted as directed.

Solution flow rate	3 plus gallons per minute
Solution pressure	Determined by faucet water pressure, averages 45 psi
Solution temperature	Determined by water source temperature
Solution recovery rate	94%
Pump discharge capacity	240 gallons per hour
Adjustable pre-sprayer	0.5 to 12 oz. per gallon
Pre-Sprayer	Handle mounted 25' hose; adjustable head
Cleaner injection	Cleaner is automatically injected into solution @ 2 oz/gal
Vacuum shoe width	14 inches
Operating weight	36 pounds
Full vacuum response	0.33 seconds
Accessories	50' hose assemblies; hose reel; upholstery tool with 5' vacuum/solution hose
Electrical requirements	110v, 13 amp circuit
Warranty*	One year parts and labor on all components
*See the actual Warranty for complete details	